



**TECHNICAL DATA :**

Filter Area	(m <sup>2</sup> )	3.5
Filter Rate	(m <sup>3</sup> /hr/m <sup>2</sup> )	15 - 42
Flow Range	(m <sup>3</sup> /hr)	53.5 - 147
Req'd B.W Flow Rate	(m <sup>3</sup> /hr/m <sup>2</sup> )	42
B.W Flow	(l/sec)	41
Wash Water Consumption	(m <sup>3</sup> )	9.8
Max Operating Pressure	(kPa)	200
Test Pressure	(kPa)	350
Shipping Weight	(kgs)	260
Service Weight	(kgs)	6100

**MEDIA REQUIREMENTS :**

Substrate Media	Nom 3.0mm - 6.0mm Gravel (Grade 5)
Substrate Qty (m <sup>3</sup> )	0.39 (625 kgs)
Filter Media	Nom 0.8mm - 2.0mm Sand (Grade 6.5)
Media Qty (m <sup>3</sup> )	1.81 (2900 kgs)

Note: Media grade size as supplied by River Sand Pty Ltd or approved equal.

**NOTES :**

1. Refer to CGF for possible Backwash valving options.
2. Filters to be installed and operated in accordance with manufacturers instructions.
3. Higher test pressures available upon request.
4. Available options include air scour, ancillary connections, sight glass, etc.
5. Filters supplied with pressure gauge, air release, vacuum breaker, access hatch and screened drain.

This document and all information and data disclosed herein is the confidential and proprietary property of CHADSON GRANULAR FILTERS and is not to be used, reproduced or disclosed in whole or in part, by or to anyone without the written permission of CHADSON GRANULAR FILTERS.

Whilst this data represents the latest information available at the time of printing, CHADSON GRANULAR FILTERS assumes no liability for its use.



Title:

**Sales Outline  
Filter Model MHS-3500**

Date: 22/10/03

DRG. No.

Scale: 1:25

F219-3500

A3