

TECHNICAL DETAILS				
NOM Filter Area (m2)	55.0			
Flow Rate (m3/hr)	138 - 269			
Required Back Wash (It/Sec)	75			
Number of Candles	7 x 7 Core 180 x 8 Core			
Effluent & Backwash size (mm)	200			
Influent Nozzle (mm)	200			
Flange Details	AS-2129 Table E			
MIN Wash Water (m3)	9.0			
Redox RS 400 (Min kgs)	30			
Shipping (m3)	6.7			
Shipping (kgs)	1470			
Service Weight (kgs)	4610			
Test Pressure (kPa)	350			
Max Operating Pressure (kPa)	200			
Filter Shell	Gr316 Stainless Steel			
Vessle Class/Code	AS - 1210			

NOTES;

- 1. Backwash pipe can be rotated to a position that suits specific project requirements. Standard location is at 0° rear. Specify angle required i.e., 45°, 180° front etc. See Plan View.
- 2. Dimensions subject to change without notice.
- All dimensions subject to shop details and/or specific project requirements.
- 4. Face plumbing, valves etc by installing contractor.
- 5. All material (UNO) To be grade 316L S/S. Fully Welded.

SERVICE CLEARANCE NOTE

Service crane drawn is for multiple filter installations enabling the lid/pressure plate (of the filter being serviced) to be moved above and over the other filters in the filter bank.

Service Height Detail:

No Overhead Crane - Lift 150mm and move away from the tank Using Overhead crane - Lift min. of 800mm for filter service and or clearance of surrounding tanks.

CHADSON ENGINEERING

15 CRESSAL ROAD BALCATTA W.A 6021 TEL. (08) 9344 3611 Fax. (08) 9344 5799 ALL EQUIPMENT, DESIGN AND APPLICATIONS SHOWN HEREIN ARE STRICTLY PRIVATE AND CONFIDENTIAL AND THE PROPERTY OF CHADSON ENGINEERING, NO USE OR DISCLOSURE THEREOF MAY BE MADE WITHOUT OUR PERMISSION IN WRITING

CLIENT					
PCT-550					
DRAWN BNC	DATE OCT18	DRAWING No.		REV SHEET SIZE	
CKD:		APPD:	SCALE		A3